

K3 SCALPER



TECHNICAL SPECIFICATIONS

Feed hopper

Capacity	3,5 m ³
Discharge height	2.410 mm

Plate apron feeder

Dimension (width x length)	1.000 x 3.150 mm
Feed capacity	Up to 250 t / h

Vibrating screen

Screen type	Double deck
Dimension (width x length)	1.200 x 2.700 mm

Belt conveyor

Fine fraction conveyor (width x length)	650 x 8.000 mm (Hydraulically foldable)
Middle fraction conveyor (width x length)	650 x 8.000 mm (Hydraulically foldable)
Coarse conveyor (width x length)	1.000 x 5.000 mm (Hydraulically foldable)

Track-unit

Dimension (width x length)	400 x 2.965 mm
2 speeds	1,1 / 1,9 km / h

Engine unit

Power	55,4 kW / 1.800 rpm
Fuel tank	280 l
Hydraulic oil tank	220 l

Control

Type	PLC - IP67
Display	3,5" LCD
Controller	Remote control

OPTIONS

Magnetic separator

Magnetic power	400 GAUSS (250 mm distance)
----------------	-----------------------------

Anti clogging system

Application	Separation of sticky material
-------------	-------------------------------

Screen flow brake

Application	Increase screening efficiency
-------------	-------------------------------

Picking station

Position	On either side
----------	----------------

Radio remote control

Type	Handheld, multi functions remote control
------	--

Working light

No. of lamps	4 pieces
--------------	----------

OPTIONAL MODEL

K3_e scalper hybrid version

TRANSPORT DIMENSIONS AND WEIGHT

Length	: 9.800 mm
Height	: 3.120 mm
Width	: 2.550 mm
Weight	: 17 t without options

