

H4 Cone Crusher



Performance highlights

- Can be used in secondary, tertiary or quarternary crushing
- Designed to crush the toughest of rock and ore
- Feed size up to 185 mm (7")
- C.S.S min. - max. 6 - 38 mm (2/10"-1 5/10"), depending on crushing chamber configuration
- Capacity up to 208 tonnes / hour
- Hopper 8 m³ (10 yard³)
- Other configurations possible with different crushing chambers
- Diesel / electric drive
- 2 speed track drive
- Optional pre screen 1.200 mm (4') x 1.800 mm (6') *not available in the United States
- Optional 3-deck screen 3.600 mm (12') x 1.500 mm (5')
- Effective screen area 5,4 m² on each deck, with return conveyor
- Best product shape
- Extensive option list to configure to your application
- Removable engine /generator compartment

Specifications

	Transport Dimensions	Transport Dimensions w/after screen	Working Length w/o after screen	Working Length with after screen
Weight:	38 t (41 sT)	46 t (50 sT)		
Length:	14.475 mm (47'6")	18.500mm (60'8")		19.400mm (63'8")
Height:	3.450 mm (11'4")	3.450mm (11'4")	4.100mm (13'5")	4.765mm (15'8")
Width:	3.000 mm (9'10")	3.000mm (9'10")	3.450mm (11'4")	11.100mm (32'10")