

R5e



Performance highlights

- R5e, electric plug-in & plug-out possibility, with drop off engine-gen set unit
- Hopper 5 m³ (6,5 yard³)
- Independent 2-deck pre-screen 2.200 x 1.000 mm (7' x 3')
- Due to long pre screen, higher crushing capacities and less wear
- Inlet opening (H x W) 800 x 1.050 mm (31" x 41")
- Rotor diameter 1.260 mm (50"), rotor width 1.000 mm (39")
- Swiveling oversize return conveyor / stockpile conveyor
- Optional double deck after screen 4.760 x 1.500 mm (15'7" x 5'), 7m³
- Tilting chassis
- Capacity up to 400 tons / hour
- 2 speed track drive
- Highest reduction ratio
- Superior product shape
- Extensive option list to configure to your application
- Optional windsifter

Specifications

	Transport dimensions	Transport dimensions w/after screen	Working length w/o after screen	Working length w/after screen
Weight	44,5 t (46 sT)	55,8 t (61 sT)		
Length	16.375mm (53'9")	17.100mm (56'1")	16.062mm (52'8")	19.361mm (63'6")
Height	3.500mm (11'6")	3.500mm (11'6")		
Width	3.000mm (9'10")	3.000mm (9'10")		