

CREATE VALUABLE PRODUCTS

Equip your Model 3680XP with a variety of teeth and screens to meet your specific end product spec. The Beast can be set up to take your waste wood and convert it to a valuable product that customers will pay top dollar for! And as your needs change, so can The Beast. Configure everything from the infeed speed, mill configuration and screens to meet your spec.

PRODUCE MORE. PAY

The Beast's patented cuttermill utilizes a unique cutterbody holder that regulates the size of the cut. The result is a more uniform product using less energy to process material. This results in savings in fuel, wear and tear, and most importantly – time – because you get the right size on the first pass.

Standard & Custom Colors Available

Choose from six standard colors, or select a custom color to match your fleet.













MAXIMUM UPTIME

The Model 3680XP is built to stand up to any daily grind. Solid steel welded construction and the industry's best components combine to create a machine professionals can trust to perform. And when you need parts or service, turn to our worldwide network of authorized dealers who are ready to offer their support.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178



Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

SPECIFICATIONS

MEASUREMENTS		3680XP TRACK	
Length:	37'3"	1135.4 cm	
Width:	11'7"	353.06 cm	
Height:	12' 2"	370.8 cm	
Weight:	84,940 lbs. (38,528.1 kg)		
Engines:	540-875 HP (402.7-652.5 kW)		
Fuel Tank:	300 gal. (1135.6 L)		
Hydraulic Tank:	150 gal. (568 L)		

UNDERCARRIAGE AND TRACK OPTIONS

Track: 325EL Steel tracks equipped with Caterpillar track under carriage, and triple grouser shoes. 3.3 MPH (5.3km/h), 13.68" (34.75 cm)

DIMENSIONS					
Capacity:	35" Capacity	88.9 cm Capacity			
Opening:	35" tall x 60" wide	88.9 cm x 152 cm wide			
Cuttermill:	42" dia. x 63" wide	106.7 cm dia. x 160 cm wide			
Teeth:	30 or 60				
Feed Wheel:	(1) 20" dia. x 59" wide	(1) 50.8 cm x 149.9 cm wide			
Infeed Conveyor: Adjustable speed 10' - 60'/min. (305-1,829 cm/min.), 14'9" long x 60" wide (449.6 cm long x 152.4 cm wide)					
Discharge Conveyor: 30' long x 48" wide (914.4 cm long x 122 cm wide), (up to 313-634 FPM conveyor speed, stacking height 19' (579.12 cm)					

ENGINE OPTION 1	ENGINE OPTION 2	ENGINE OPTION 3
Make and Model: CAT C15	Make and Model: CAT C18	Make and Model: CAT C27
Gross HP: 540 HP (402.7 kW)	Gross HP: 755 HP (563 kW)	Gross HP: 875 HP (652.5 kW)
Fan: Reversing	Fan: Reversing	Fan: Reversing
Clutch Type: HPTO14 PT Tech fluid	Clutch Type: HPTO14 PT Tech fluid	Clutch Type: HPT014 PT Tech flu

COMMITTED TO QUALITY & SERVICE

The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipper –regardless the age, hours, or warranty status – the Bandit Backbone is here to support you.

We Are Here to Support You

There are nearly 200 dealer locations in the US and 61 international dealers to support you. They are factory trained. Plus we have an experienced parts and service department supporting you and our dealers.

GO-ANYWHERE TRACK MOBILITY

Caterpillar 325EL steel track undercarriage can be added to the 3680XP. This feature allows it to travel over rough terrain not accessible by towable units. It also eliminates the need to forward or skid material to the grinder – the operator can take the grinder to the trees.



101411 Ioon nata

When you choose a Bandit, you'll experience more uniform end product production, smoother and more efficient grinder, long-lasting components and improved fuel economy. We invite you to see for yourself by scheduling a demo with your nearest authorized Bandit dealer.



Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments